



DECLARATION OF PERFORMANCE (Regulation (EU) No 305/2011)

FIRE DAMPERS TO EN 15650

Products intended for heating, ventilation and air conditioning installations in buildings to prevent fire propagation

Certificate of conformity:	0370-CPR-2591			
MODEL:	SCFR-GD			
MANUFACTURER:	SAFEAIR S.L. (KOOLAIR GROUP)			
	Polígono San Isidro, 45223 Seseña, Toledo, Spain			
NOTIFIED BODY:	0370 - LGAI - Technological Center, S.A.			
"The notified product certification body	has performed the determination of the product-type on the basi			

"The notified product certification body has performed the determination of the product-type on the basis of type testing, the initial inspection of the manufacturing plant and of factory production control, and continuous surveillance, assessment and evaluation of factory production control, in compliance with SYSTEM 1 of the Spanish Technical Building Code (CTE)"

Testing to EN 1366-2 (16/12065-2107; 16/12065-1305, 3P08908-4, 13-5709-3596, 17/14004-348)

PERFORMANCE DECLARED:

Size (mm)	Execution	Mounting	Test pressure	EN 13501-3 Classification			
≥ 200 x200 ≤ 1500 x 800	Rigid wall	Vertical	500 Pa	El 120 (ve i ↔ o) S			
≥ 850 x200 ≤ 1500 x 800	Floor slab	Horizontal		El 120 (ho i ↔ o) S			
4.2.1.2 Nominal activation conditions/sensitivity:							
4.2.1.2.2 Sensing element load-bearing capacity					Passed		
4.2.1.2.3 - Sensing element temperature response							
4.2.2.2 Response delay (response time):			Closure time	Э	Passed		
4.3.1.a Operational reliability:			Cycles	Cycles			
Fire resistance:							
Integrity			4.1.1.a)		El 120 (ve i ↔ o) S		
Insulation			4.1.1.b)				
Leakage flow			4.1.1.c)	4.1.1.c)			
Mechanical stability (under E)			4.1.1.d)	El 120 (ho i ↔ o) S			
Maintenance of the cross-section (under E)			4.1.1.e)				
4.2.1.2.2/3 Durability of response delay:							
4.2.1.2.2 Sensing element temperature response					Passed		
4.2.1.2.3 Element load-bearing capacity							
4.3.3.2 Durability of operational reliability: Open/close testing				N	Notor-driven: 10,000 cycles		
					Manual: 300 cycles		

We hereby state that the **SCFR-GD** firewall damper complies with the performance listed above. This declaration is issued under the sole responsibility of the manufacturer.

In Madrid, 26 October 2018 José Tomás Susarte Torrijos General Manager, Koolair Group